Delock DisplayPort Tester for EDID information with OLED display

Description

This DisplayPort tester with OLED display by Delock is used to read the EDID data stored in the monitor. The OLED display shows the maximum resolution, the refresh rate, the HDCP status, the transmission rate and the color depth of the connected device.

Note

The tester is powered by the graphics card. The included 20 pin Displayport cable can be used for extension.



Item no. 63338

EAN: 4043619633388

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  1 x DisplayPort 20 pin male >
  1 x DisplayPort 20 pin female
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Signal routed to the output (pass-through)
- Double row OLED display
- Plastic housing
- Colour: black
- Dimensions incl. connector (LxWxH): ca. 72.5 x 22.0 x 11.0 mm

System requirements

- A free DisplayPort female

Package content

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- DisplayPort EDID Tester
- DisplayPort extension cable, length ca. 35 cm
- User manual

Images









© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	HDCP 1.3 HDCP 1.4 HDCP 2.2

Interface

connector:	1 x DisplayPort male
Connector 1:	1 x DisplayPort female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Length:	72.5 mm
Width:	22 mm
Height:	11 m

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.