

# Delock Adapter USB Type-C™ > 1 x Serial DB9 RS-232

## Description

This USB Type-C™ to serial adapter by Delock provides a compatible RS-232 DB9 interface for printers, measuring instruments, controllers, IoT devices etc.



ca. 25 cm

## Specification

- Connectors:
  - 1 x USB Type-C™ male
  - 1 x serial RS-232 DB9 male
- Chipset: FTDI FT232RL
- Serial connector with nuts
- Data transfer rate up to 460.8 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Cable type: UL 444
- Cable length without connectors: ca. 15 cm
- Colour: black

## System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.13 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ or Thunderbolt™ 3 port

## Package content

- USB Type-C™ to 1 x serial adapter
- Driver CD
- User manual

Item no. 63908


EAN: 4043619639083

Country of origin: China

Package: Retail Box



## Images



| General                       |  |
|-------------------------------|--|
| Function:                     | Plug & Play  |
| Specification:                | RS-232 (EIA / TIA)<br>Thunderbolt™ 3<br>USB Type-C™  |
| Supported operating system:   | Windows 7 32-bit<br>Windows 7 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Mac OS 10.13 or above<br>Linux Kernel 2.6 or above |
| Interface                     |  |
| Output:                       | 1 x serial RS-232 DB9 male   |
| Input:                        | 1 x USB Type-C™ male   |
| Technical characteristics     |  |
| Chipset:                      | FTDI FT232RL   |
| Data transfer rate:           | up to 460,8 Kbps   |
| FIFO:                         | 1 x 256 byte receiver<br>1 x 128 byte transmit   |
| Data transmission:            | asynchronous<br>full duplex  |
| UART:                         | USB to serial UART   |
| Physical characteristics      |  |
| Cable type:                   | UL 444   |
| Cable diameter:               | 4.4 mm   |
| Cable length incl. connector: | 25 cm  |
| Pin finishing:                | gold-plated  |
| Conductor gauge:              | 28 AWG data line<br>24 AWG power line  |
| Screw type:                   | #4-40 UNC  |
| Shielding:                    | double   |
| Colour:                       | black  |