

Delock Prilagodnik USB Type-C™ > 1 x serijski DB9 RS-232

Opis

Ovaj prilagodnik USB Type-C™ na serijski tvrtke Delock pruža kompatibilno sučelje RS-232 DB9 za pisače, mjerne instrumente, upravljače, IoT uređaje, itd.



ca. 25 cm

Tehnički podaci

- Priključak:
 - 1 x USB Type-C™, muški
 - 1 x serijska muška RS-232 DB9
- Skup čipova: FTDI FT232RL
- Serijski priključci s maticama za vijke
- Brzina prijenosa podataka do 460,8 Kbps
- Signali: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Vrsta kabela: UL 444
- Duljina kabela bez konektora: oko 15 cm
- Boja: crno

Preduvjeti sustava

- Linux Kernel 2.6 ili noviji
- Mac OS 10.13 ili noviji
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Osobno ili prijenosno računalo sa slobodnim priključkom USB Type-C™ ili priključkom Thunderbolt™ 3

Sadržaj pakiranja

- USB Type-C™ na 1 x serijski adapter
- CD s upravljačkim programom
- Korisnički priručnik

Predmet br. 63908


EAN: 4043619639083

Zemlja podrijetla: China

Pakiranje: Retail Box



Slike





General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) Thunderbolt™ 3 USB Type-C™
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac OS 10.13 o superiore Linux Kernel 2.6 o superiore
Interface	
Output:	1 x RS-232 DB9 seriale maschio
Input:	1 x USB Type-C™ male
Technical characteristics	
Chipset:	FTDI FT232RL
Data transfer rate:	up to 460,8 Kbps
FIFO:	1 x 256 byte receiver 1 x 128 byte transmit
Data transmission:	asynchronous full duplex
UART:	USB to serial UART
Physical characteristics	
Cable type:	UL 444
Cable diameter:	4,4 mm
Cable length incl. connector:	25 cm
Pin finishing:	gold-plated
Conductor gauge:	28 AWG data line 24 AWG power line
Tipo di vite:	#4-40 UNC
Shielding:	double
Colour:	nero