

Delock Adaptor USB Type-C™ > 1 x interfață serială DB9 RS-232

Descriere scurta

Acest adaptor USB Type-C™ la serial de la Delock oferă o interfață compatibilă RS-232 DB9 pentru imprimante, instrumente de măsură, controale, dispozitive IoT etc.



ca. 25 cm

Specificatii

- Conectori:
 - 1 x USB Type-C™ tată
 - 1 x RS-232 seriale DB9 tată
- Chipset: FTDI FT232RL
- Conector serial cu piulițe
- Rată de transfer a datelor de până la 460,8 Kbps
- Semnale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Tip cablu: UL 444
- Lungime cablu fără conectori: cca 15 cm
- Culoare: negru

Cerinte de sistem

- Linux Kernel 2.6 sau superior
- Mac OS 10.13 sau superior
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC sau laptop cu un port USB Type-C™ sau Thunderbolt™ 3 liber

Pachetul contine

- USB Type-C™ la 1 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Nr. 63908


EAN: 4043619639083

Țara de origine: China

Pachet: Retail Box



Imagini



General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) Thunderbolt™ 3 USB Type-C™
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac OS 10.13 sau superior Linux Kernel 2.6 sau superior
Interface	
Output:	1 x RS-232 seriale DB9, tată
Input:	1 x USB Type-C™ male
Technical characteristics	
Chipset:	FTDI FT232RL
Data transfer rate:	up to 460,8 Kbps
FIFO:	1 x 256 byte receiver 1 x 128 byte transmit
Data transmission:	asynchronous full duplex
UART:	USB to serial UART
Physical characteristics	
Cable type:	UL 444
Cable diameter:	4,4 mm
Cable length incl. connector:	25 cm
Pin finishing:	gold-plated
Conductor gauge:	28 AWG data line 24 AWG power line
Tipul șurubului:	#4-40 UNC
Shielding:	double
Colour:	negru