
Delock DisplayPort 1.2 Splitter 1 x DisplayPort in > 2 x DisplayPort out 4K

Description

This splitter by Delock receives a DisplayPort signal from a PC or laptop and splits it to two connected displays. Thereby one DisplayPort connection can be used to operate two DisplayPort monitors. Both outputs are dual-mode capable (DP++), so that HDMI or DVI monitors can be connected with suitable adapters.



Note

The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.

Item no. 87665

EAN: 4043619876655

Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

- Connectors:
  Input:
  1 x DisplayPort 20 pin male
  Output:
  2 x DisplayPort 20 pin female
- Chipset: STDP4320
- DisplayPort 1.2a specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Functions: Mirrored or Extended (Windows only)
- Maximum resolution (depending on the system and the connected hardware):
  DisplayPort 1.1 or 1.2 Single Stream Transport (SST):
  up to 1920 x 1080 @ 60 Hz (mirror)
  DisplayPort 1.2 Multi Stream Transport (MST):
  up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (mirror or extended)
- DisplayPort output supports Dual Mode DP++
- Supports Eyefinity / Single Large Surface (SLS)
- Audio input formats: 7.1 channel up to 192 kHz sample rate
- Metal housing

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Colour: black
- Cable length without connectors: ca. 30 cm
- Dimensions (LxWxH): ca. 100 x 67 x 23 mm


System requirements

- Windows 8.1/8.1-64/10/10-64, Mac ex OS 10.12
- One free DisplayPort female

Package content

- DisplayPort Splitter
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	DisplayPort 1.2a

Interface

Output:	2 x DisplayPort female
Input:	1 x DisplayPort male

Technical characteristics

Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Housing material:	metal
Cable length incl. connector:	30 cm
Length:	100 mm
Width:	67 mm
Height:	23 mm
Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.