
Delock PCI Express x1 Card 2 x RJ45 Gigabit LAN RTL8111

Description

The PCI Express card by Delock offers two network ports with a data transfer rate up to 1000 Mbps.



Item no. 89999

EAN: 4043619899999

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  external: 2 x Gigabit LAN RJ45 jack
  internal: 1 x PCI Express x1, V1.1
- Chipset: Realtek RTL8111H, ASMedia ASM1182e
- Data transfer rate:
  Ethernet up to 10 Mbps (Half/Full Duplex)
  Fast Ethernet up to 100 Mbps (Half/Full Duplex)
  Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
  PCI Express x1 up to 2.5 Gbps
- Compatible with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Supports Wake On LAN (WOL)
- Supports IEEE 802.1P layer 2 priority encoding
- Supports IEEE 802.3x full duplex flow control
- Supports IEEE 802.1Q Virtual LAN (VLAN)

System requirements


© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Linux Kernel 3.10 or above
- Mac OS 10.5 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free PCI Express slot

Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Supported operating system:	Linux Kernel 3.10 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

External:	2 x Gigabit LAN RJ45 jack
Internal:	1 x PCI Express x1, V1.1

Technical characteristics

Chipset:	Realtek RTL8111H
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps

Physical characteristics

Slot bracket:	Low Profile standard

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.